


## Vandal Proof AHD Camera

NVAHD-4DN3202V/IR-1

**3000**  
AHD SERIES



### KEY FEATURES



### KEY FEATURES

- Funcție zi/noapte - filtru IR mecanic
- rezoluție 4MPX
- Lens: varifocala, f=2.8 ~ 12 mm/F1.4
- Min. Illumination: 0.03 lx (0 lx, IR on)
- Led-uri IR, distanta iluminare pana la 25 m

### DIMENSIUNI



<b>Imagine</b>	
Senzor imagine	1/3" OV
Mod operare	AHD 4MPX
Numar de pixeli efectivi	2560 (H) x 1440 (V)
Rezolutie	4MPX
Iluminarea minimă	0.03 lx/F1.4 - mod de culoare, 0 lx (cu IR pornit) - B/W mod
Raport semnal/zgomot	> 50 dB (AGC oprit)
Shutter electronic	auto: 1/25 s ~ 1/50000 s
Wide Dynamic Range (WDR)	da
Digital Noise Reduction (DNR)	2D
<b>Lentila</b>	
Tip lentila	varifocala, f=2.8 ~ 12 mm/F1.4
<b>Zi/Noapte</b>	
Mod comutare	mecanic cu filtru IR
Modul de comutare	auto, manual
Întârzierea de comutare	0 ~ 60 s
Senzor lumina vizibil	Astfel
<b>Alte functii</b>	
OSD	limba: Poloneza, Engleza, Rusa, altele
Procesare imagine	Corectie pixeli morti (DPC), corectarea efectului vignetting, rotire imagine la 180°, sharpening, efectul oglinda
Telecomanda	Da (COAX protocol)
<b>Led-uri IR</b>	
Numar Led-uri	40
Distanta	25 m
Unghi	120°
<b>Interfata</b>	
lesire video	BNC, 1.0 Vp-p, 75 Ohm
<b>Parametri instalare</b>	
Dimensiuni (mm)	151 (Ø) x 113 (H)
Greutate	0.7 kg
Grad protectie	IP 66 (details in the user's manual)
Carcasa	vandal proof aluminiu, alb
Alimentare electrica	12 VDC
Consum de energie	1 W, 5 W (cu IR pornit)
Temperatura de functionare	-20°C ~ 55°C

Access to the OSD and enable/configuration camera options require the use of AHD DVR with COAX function